



interfis

GRUPA ELHURT

www.interfis.com.pl

www.interfis.com.pl

www.interfis.com.pl

Laser Barcode Reader LC2200



Functionality Item	Performance Parameter
Type of illuminant	650nm laser
Use type	Hand-held or bracket-held installation
Bit error rate (BER)	1/5 million
Safety performance	Meet the Grade II National Criteria for Laser Safety
Barcode types	EAN-8,EAN-13,UPC-A,UPC-E,Code 39,Code 93,Code128,EAN128,Codaber,Industool 2 of 5,Interleave 2 of 5,Matrix 2 of 5,MSI, Chinese postcode etc.
Supported interfaces	RS232, PC2 keyboard, USB, etc.
Scanning method	Manual,can set to be Continuous Automatic Scan
Transmission rate	RS232 Baudrate:2400-38400
Resolution (pcs0.9)	0.10mm(4mil)
Depth of field	10-420mm (pos09 density 0.25)
Materials	ABS+PC
Reading speed	100 times/second
Reading preciseness	0.40-0.825mm
Reading distance	10-520mm
Reading angle of elevation	60°
Reading angle of dip	45°
Operating temperature	-20°C-45°C
Storage temperature	20°C-45°C
Operating humidity	5%-85%
Storage humidity	5%-85%
Power voltage	5V
Working current	57mA
Static current	36mA
Fall test m	100 times/1.5
Light intensity	Daylight, 4000Lux
Electromagnetic interference	Complying with en50081, par1 criteria
External electromagnetic	Complying with en50081, par1 criteria
Dustproofing and waterproofing	Complying with en50081, par1 criteria



Interfis Sp. z o.o.
 ul. Galaktyczna 35A, 80-299 Gdańsk
 Tel. +48 58 554 0849; Fax +48 58 554 0806
interfis@interfis.com.pl www.interfis.com.pl
 Opracowała: Dagmara Pasierbska